



Quality Access Doors- **FAST!**

STANDARD OPTIONS

MATERIAL:

16 gauge cold rolled steel

HINGE:

Continuous piano hinge.

Note: Hinge on second dimension (Height)

LOCK / LATCH:

Screwdriver operated cam latch

FINISH:

High quality white powder coat primer

PACKAGING:

Individually wrapped, 1 per box

OPTIONS AVAILABLE

MATERIAL:

Stainless steel 304 #4 (brushed finish)

For a complete list of options visit
www.BestAccessDoors.com

Scan  or  Click



To view Pricing and
Additional Product Info.

**LEED READY: THIS PRODUCT
CONTRIBUTES TO LEED® CREDITS**



SUBMITTAL/TECHNICAL DATA SHEET


SKU: **BA-SMD**

SURFACE MOUNTED DOOR



■ INSTALLATION


>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)



■ DIMENSIONS AND APPEARANCE

DOOR SIZE W x H INCHES (MM)	CLEAR INSIDE OPENING INCHES (MM)	NUMBER OF LOCKS	WEIGHT LBS KG
8 x 8 (203 x 203)	7 3/4 x 7 (197 x 178)	1	3 1.4
12 x 12 (304 x 304)	11 3/4 x 11 (298 x 279)	1	5 2.3
*16 x 16 (406 x 406)	15 3/4 x 15 (400 x 381)	1	8 3.6
*18 x 18 (457 x 457)	17 3/4 x 17 (451 x 432)	1	12 4.5
*24 x 24 (609 x 609)	23 3/4 x 23 (603 x 584)	1	15 6.8

*(NOT RECOMMENDED FOR CEILING)



■ PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com