



SUBMITTAL/TECHNICAL DATA SHEET

STANDARD OPTIONS

MATERIAL:
16 gauge cold rolled steel

HINGE:
Concealed, Exclusive hinge design.
Note: Hinge on second dimension (Height)

LOCK / LATCH:
Screwdriver operated cam latch

FINISH:
High quality white powder coat primer

PACKAGING:
Individually wrapped, 1 per box

OPTIONS AVAILABLE

LOCK / LATCH:

- Key operated cylinder cam latch
- Hex head cam latch
- Pinned hex head cam latch
- Handle operated cam latch
- Mortise preparation for cylinder

MATERIAL:
Stainless steel 304 #4 (brushed finish)

GASKETING:
Neoprene gasket

SKU: **BA-UHF**


AESTHETIC ACCESS DOOR

WITH HIDDEN FLANGE



■ INSTALLATION

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<



■ DIMENSIONS AND APPEARANCE

For a complete list of options visit
www.BestAccessDoors.com


Scan  or  Click



To view Pricing and
Additional Product Info.

**LEED READY: THIS PRODUCT
CONTRIBUTES TO LEED® CREDITS**

DOOR SIZE W x H INCHES (MM)	NUMBER OF LOCKS	WEIGHT LBS KG	
8 1/4 x 8 1/4 (210 x 210)	1	3	1.4
8 1/4 x 12 (210 x 304)	1	4	1.8
10 x 10 (254 x 254)	1	4	1.8
12 x 12 (304 x 304)	1	6	2.7
14 x 14 (355 x 355)	1	7	3.2
12 x 18 (304 x 457)	1	8	3.6
16 x 16 (406 x 406)	1	9	4.1
18 x 18 (457 x 457)	3	10	4.5
18 x 24 (457 x 609)	4	13	5.9
20 x 20 (508 x 508)	3	13	5.9
22 x 22 (558 x 558)	3	15	6.8
22 x 30 (558 x 762)	5	17	7.7
22 x 36 (558 x 914)	5	19	8.6
24 x 24 (609 x 609)	4	17	7.7
24 x 30 (609 x 762)	5	19	8.9
24 x 36 (609 x 914)	5	24	10.9



ROUGH WALL OPENING IS DOOR SIZE + 1/4" OR + 6MM

■ PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com